

FLP-900-20

Safety Certifications



Technical Specifications




10.5"-

4.25"

Jaic	ety certifications	·
CE I	Mark of Declaration	
Wat	terproof Certification	ı
IP 6	5 (Waterproof)	
Dim	nensions	
•	Height	25"
•	Diameter	2.125"
•	Base Dimensions	3.5" X 3.5", base flange is .25" with 5mm holes for mount
•	Beam	180°
•	Net Weight	5 lbs
Mat	terial Specifications	
•	Metal	Anodized aluminum
•	Gaskets	Neoprene polymer located at base
•	Lens	Polycarbonate/Lexan
Elec	ctrical Specifications	
•	Voltage	120
•	Cycle	60 hz
•	Ballast	Magnetic coil ballast, located in base
•	Amperage	.2
•	Wattage	13
•	Kelvin (color temperature)	4,100
•	On/off switch	Push button at end cap
Cor	d Specifications	
•	Certification	SJT (oil resistant)
•	Length	6′
•	Plug	Standard grounded US 3 prong male plug. (NEMA 5-15)
•	Composition	16 gauge 3-conductor copper wiring, SJT (oil resistant) certified neoprene jacket
Acc	essories/Options	
•	Lens	Glass tube lens
•	Mounting Brackets	HLP-22, HLP-24-005, HLP-29-005, HLP-30 (All Pictured Below) HLP-22-2000 (Not Shown)
•	Bulbs	PL-13/41CW
		<u> </u>

Products specifications are subject to change.













HLP-22-2000

HLP-24-005

HLP-29-005

HLP-30



→ 3¹/₃-1

1" Beads

HALOGEN LIGHTING PRODUCTS CORPORATION $^{^{TM}}$