

HLP-005-20

Safety Certifications



Technical Specifications



CE I	Mark of Declaration	
Wat	terproof Certification	
IP 5	4 (Splashproof)	
Dim	nensions	
•	Height	28.375"
•	Head Diameter	2.875"
•	Base Dimensions	3.5" X 3.5", base flange is .25" with 5mm holes for mount
•	Beam	36°
•	Net Weight	5 lbs
Mat	terial Specifications	
•	Metal	Anodized aluminum
•	Gaskets	Neoprene polymer located at base
•	Lens	Tempered borosilicate glass
Elec	ctrical Specifications	
•	Voltage	120 VAC
•	Cycle	60 hz
•	Transformer	Magnetic coil, located in base
•	Amperage	.34
•	Wattage	35
•	Kelvin (color tem- perature)	4,100
•	On/off switch	Rocker switch located on handle, dimmable switch at base
Cor	d Specifications	
•	Certification	SJT (oil resistant)
•	Length	6′
•	Plug	Standard grounded US 3 prong male plug. (NEMA 5-15)
•	Composition	16 gauge 3-conductor copper wiring, SJT (oil resistant) certified neoprene jacket
Acc	essories/Options	
•	Mounting Brackets	HLP-22 HLP-24-005, HLP-29-005, HLP-30 (All Pictured Below) HLP-22-2000 (Not Shown)
•	Bulbs	HLP-35-MR16-12
		1

Shown mounted with HLP-24-005 magnet (Not included)

1" Beads

Optional Accessories:











Product specifications are subject to change.

HLP-24-005 HLP-29-005





4.25"

HALOGEN LIGHTING PRODUCTS CORPORATION $^{\mathsf{TM}}$