



**THE
TOUGH
GUY™**

HLP-1000L



Technical Specifications



| Safety Certifications | |
|-----------------------------------|---|
| CE Mark of Declaration | |
| Waterproof Certification | |
| IP 67 (Waterproof under pressure) | |
| Dimensions | |
| • Height | 46.375" |
| • Head Diameter | 4.875" |
| • Base Dimensions | 3.5" X 3.5", base flange is .25" with 5mm holes for mount |
| • Beam | 67° |
| • Net Weight | 7 lbs |
| Material Specifications | |
| • Metal | Anodized aluminum |
| • Gaskets | Neoprene polymer located at glass, base, and switch |
| • Lens | Tempered borosilicate glass |
| Electrical Specifications | |
| • Voltage | 24 VDC |
| • Cycle | N/A, |
| • Transformer | N/A, wires directly into power source |
| • Amperage | .6 |
| • Wattage | 75 |
| • Lumen rating | 1,350 at 75 watts |
| • Kelvin (color temperature) | 4,100 |
| • On/off switch | Toggle switch located on the back of light head |
| Cord Specifications | |
| • Certification | SJT (oil resistant) |
| • Length | 6' |
| • Plug | N/A, wires directly into power source |
| • Composition | 16 gauge 3-conductor copper wiring, SJT (oil resistant) certified neoprene jacket |
| Accessories/Options | |
| • Lens | Frosted glass |
| • Mounting Brackets | HLP-22-2000, HLP-24-005, HLP-29-005, HLP-30 (All Pictured Below) HLP-22-2000 (Not Shown) |
| • Bulbs | HLP-75-BI-24, HLP-100-BI-24, HLP-70-H3-24 |
| • Miscellaneous | BI-PIN KIT |

Products specifications are subject to change.

Optional Accessories:

Extended Height = 46.375"



HLP-22



HLP-24-005



HLP-29-005



HLP-30



HALOGEN LIGHTING PRODUCTS CORPORATION™

Telephone: 1-800-621-0001 • www.halogen-lighting.com