

HLP-1000M






Technical Specifications

Safe	ety Certifications	
CE I	Mark of Declaration	
Wa	terproof Certification	
IP 6	7 (Waterproof under p	ressure)
Dim	nensions	
•	Height	30.750"
•	Head Diameter	4.875"
•	Base Dimensions	3.5" X 3.5" , base flange is .25" with 5mm holes for mount
•	Beam	67°
•	Net Weight	7
Ma	terial Specifications	
•	Metal	Anodized aluminum
•	Gaskets	Neoprene polymer located at glass, base, and switch
•	Lens	Tempered borosilicate glass
Elec	ctrical Specifications	
•	Voltage	24 VDC
•	Cycle	N/A
•	Transformer	N/A, wires directly into power source
•	Amperage	.6
•	Wattage	75
•	Lumen rating	1,350 at 75 watts
•	Kelvin (color tem- perature)	4,100
•	On/off switch	Toggle switch located on the back of light head
Cor	d Specifications	
•	Certification	SJT (oil resistant)
•	Length	6'
•	Plug	N/A, wires directly into power source
•	Composition	16 gauge 3-conductor copper wiring, SJT (oil resistant) certified neoprene jacket
Acc	essories/Options	
•	Lens	Frosted glass
•	Mounting Brackets	HLP-22, HLP-24-005, HLP-29-005, HLP-30 (All Pictured Below) HLP-22-2000 (Not Shown)
•	Bulbs	HLP-75-BI-24, HLP-100-BI-24, HLP-70-H3-24
•	Miscellaneous	BI-PIN KIT

Products specifications are subject to change.



Optional Accessories:







HLP-22

360°

HLP-24-005

HLP-29-005

HLP-30



HALOGEN LIGHTING PRODUCTS CORPORATION[™]