



| | |
|--|---|
| Safety Certifications | |
| CE Mark of Declaration, RoHS Compliant | |
| Waterproof Certification | |
| IP65 (Waterproof Under Pressure) | |
| Dimensions (Arm) | |
| • Length | 42.0" |
| • Width | 4.75" at double strut, strut width 1.5" |
| • Height | 1.5" |
| • Net Weight | 13.0 pounds |
| Dimensions (Head) | |
| • Diameter | 6.5" |
| • Width | 4.0" |
| • Beam | 50° |
| • Net Weight | 6.0 pounds |
| Material Specifications | |
| • Housing | Cast Aluminum |
| • Lens | Polycarbonate |
| Electrical Specifications | |
| • Voltage | 100-240 VAC |
| • Cycle | 50/60hz |
| • Driver | Variable voltage driver located in light head |
| • Amperage | .21 @ 120 VAC |
| • Wattage | 18 |
| • Lumen rating | 1,248 |
| • Kelvin (color temperature) | 5,000 |
| • On/off switch | Toggle switch behind light head |
| Cord Specifications | |
| • Certification | SJT (oil resistant) |
| • Length | 22' |
| • Plug | Standard grounded US 3 prong male plug. (NEMA 5-15) |
| • Composition | 16 gauge 3-conductor copper wiring, SJT (oil resistant) certified neoprene jacket |

Product specifications are subject to change.

